



DPP-350 is the latest in the series of mobile printers. It is one of the smallest and lightest mobile printers in the world.

DPP-250 offers all the features of our other popular models of mobile printers, PP-50, PP-55, DP-350, yet can easily fit into your pocket.

Printing method	Line thermal printing
Total dots	576 dots/line
Dot density	8 dots/mm (203 dpi)
Print speed	60 mm/sec
Print width and characters per line	72 mm Font A: 48 characters/line Font B: 64 characters/line Font C: 48 characters/line (loadable) Font D: 64 characters/line (loadable)
Recommended paper	Thermal paper roll: - 78 mm / Ø 50 mm, thickness 60 µm; - 60 mm / Ø 50 mm, thickness 60 µm; - 57 mm / Ø 50 mm, thickness 60 µm. Label paper roll: - 78 mm / Ø 50 mm; - 57 mm / Ø 50 mm.
Interfaces	RS-232C with optional special cable (1200 – 115200 bps); USB 1.1 compatible 2.0 host / slave; Bluetooth (option) ; Wi-Fi (option).
Drivers for	Pocket PC; Palm OS; Windows; BlackBerry.
Configuration options	Magnetic Stripe Reader (option); Smart Card Reader (option); Mi FARE Reader (option); SD Card Slot for SD Card or Wi-Fi Modules (option).
Emulation	ESC/POS / LABEL Label Printing ELTRON compatible (EPL-2); label length 100 mm maximum; Barcode Printing: EAN13, EAN8, UPC-A, UPC-E, Codabar, Code 39, Code 128.

Power supply	Rechargeable battery (Li-Ion 7.4V; 2000 mAh)
Battery charge time	3 hours maximum
Print lines per charge	30,000 (fully charged)
Buffer	ESC/POS mode: 56 Kb; Label mode: 16 Kb.
Reliability	50,000,000 pulses or 50 km mechanism (MCBF): 15,000,000 lines
Weight	340 grams (w / o paper); 430 grams (with paper); 540 grams (with label paper roll).
Dimension (w) x (d) x (h), mm	108 x 111 x 62
Environment	Operating -10oC to +50oC Storage -20oC to +60oC
More features / Applications	Mobile; Traveling sales; Retail; Transportation; Receipt Printer; Point of sales; Healthcare; Warehousing; Distribution.
Accessories	Wearable built-in metal belt hook Neck / shoulder lanyard

